SAFETY JOGGER
INDUSTRIAL



Medium

JUMPER S3S

Safety Shoes With SlipResistant Grip

JUMPER provides SR slip resistance, metal-free comfort, antistatic protection and heel cushioning for secure movement across multiple industries.

Upper	Suede Leather, Textile
Lining	Recycled Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Anti-Puncture Textile
Outsole	PU
Toecap	Composite
Category	S3S / SR, SC, FO, CI
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 JPN 22.5-31 / KOR 235-310
Sample weight	0.600 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024

CO_2 11.25 kg




117

WPA

3FIT SYSTEM

NESKRID



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Antistatic
Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



SJ Foam
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



Oil & fuel resistant
The outsole is resistant against oil and fuel.

SAFETY JOGGER WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED IN EUROPE

www.safetyjogger.com

Industries:
Automotive, Cleaning, Construction, Food & beverages, Logistics, Industry

Environments:
Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Suede Leather, Textile**			
	Upper: permeability to water vapor	≥ 0.8	9.35	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	79	mg/cm^2
Lining	**Recycled Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	49.8	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	398.8	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	25600/12800	cycles
Outsole	**PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	77	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.32	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.38	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.20	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.24	friction
	Antistatic value	0.1 - 1000	79.3	MegaOhm
	ESD value	0.1 - 100	N/A	MegaOhm
	Heel energy absorption	≥ 20	37	J
Toecap	**Composite**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	15.5	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	23.0	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	8.98	kg
	Packing	0.12	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		11.25 kg CO2/pair	

	Description	Result
Recycled content		
	Product	7%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.