SAFETY JOGGER
INDUSTRIAL



Medium

MODULO PURE S3S S TG

MDLPRS3STG

Slip-On S3S Safety Shoes

The MODULO PURE slipon safety shoe is HACCPready, vegan and metalfree, with a stainresistant Lorica upper and Tiger Grip outsole for hygiene and traction.

Upper	Lorica
Lining	Recycled 3D-Mesh (100% recycled)
Footbed	SJ Recycled Foam Footbed (96% recycled)
Midsole	Anti-Puncture Textile
Outsole	Rubber (NBR), BASF PU
Toecap	Nano Carbon
Category	S3S / SR, FO, HI, HRO, CI, ESD
Size range	EU 35-50
Sample weight	0.560 kg
Norms	EN ISO 20345:2022+A1:2024 ASTM F2413:2024

CO_2 7.77 kg



WHT



BLK

Lorica
Lorica is a high-performance synthetic microfiber that offers exceptional strength and durability. It repels water, oils and stains and meets strict HACCP hygiene standards.



Tiger Grip Technology
Outsoles with Tiger Grip technology are renowned for their slip resistance, ability to withstand wear and tear and excellent traction on different surfaces, even wet and uneven ones. They are crafted with an exclusive rubber compound and engineered with specific patterns and grooves to enhance grip and stability.



Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



Electrostatic Discharge (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 100 MegaOhm.



Puncture resistant lightweight
Metal free, super flexible and ultralight puncture resistant midsole. Covers 100% of the bottom area of the last, no thermal conductivity.



Rubber outsole
Rubber outsoles provide versatile functions that make them suitable for many areas of application: excellent cut resistance, heat and cold resistance, high flexibility at cold temperatures, resistance against oil, fuel and many chemicals.

Industries:
Assembly, Catering, Chemical, Cleaning, Food & beverages, Industry, Logistics, Medical

Environments:
Dry environment, Extreme slippery surfaces, Warm surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

Test results:

	Description	EN ISO 20345	Result	Measure unit
Upper	**Lorica**			
	Upper: permeability to water vapor	≥ 0.8	1.80	mg/cm^2 /h
	Upper: water vapor coefficient	≥ 15	17	mg/cm^2
Lining	**Recycled 3D-Mesh (100% recycled)**			
	Lining: permeability to water vapor	≥ 2	18.2	mg/cm^2 /h
	Lining: water vapor coefficient	≥ 20	146.8	mg/cm^2
Footbed	**SJ Recycled Foam Footbed (96% recycled)**			
	Footbed: abrasion resistance (dry/wet) (cycles)	25600/12800	Dry 25600 cycles/Wet 12800 cycles	cycles
Outsole	**Rubber (NBR), BASF PU**			
	Outsole abrasion resistance (volume loss)	≤ 150	124	mm^3
	Basic Slip resistance - Ceramic + NaLS - Forward heel slip	≥ 0.31	0.38	friction
	Basic Slip resistance - Ceramic + NaLS - Backward forepart slip	≥ 0.36	0.45	friction
	SR Slip resistance - Ceramic + glycerin - Forward heel slip	≥ 0.19	0.23	friction
	SR Slip resistance - Ceramic + glycerin - Backward forepart slip	≥ 0.22	0.26	friction
	Antistatic value	0.1 - 1000	57.1	MegaOhm
	ESD value	0.1 - 100	69	MegaOhm
	Heel energy absorption	≥ 20	32	J
Toecap	**Nano Carbon**			
	Impact resistance toecap (clearance after impact 100J)	N/A	N/A	mm
	Compression resistance toecap (clearance after compression 10kN)	N/A	N/A	mm
	Impact resistance toecap (clearance after impact 200J)	≥ 14	17.0	mm
	Compression resistance toecap (clearance after compression 15kN)	≥ 14	23.0	mm

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Carbon footprint:

	Description	Result	Measure unit
CO2 emission			
	Material	5.56	kg
	Packing	0.05	kg
	Manufacturing	1.90	kg
	Transport	0.26	kg
		7.77 kg CO2/pair	

	Description	Result
Recycled content		
	Product	10%
	Packing	99%

CO2 calculation:
Values are rounded to two decimals.
These analyses are performed using our in-house environmental calculators, developed within the Cortina Group. The CO2 values are valid at the time of calculation and may be subject to change.